

SPRING BALANCER

*TIGON Spring Balancer Improves Work Safety & Efficiency.
Capacities ranging from 0.5~70kg.*

TIGON



MODEL	Capacity (kg)	Stroke (m)	Weight (kg)
TW-00	0.5~1.5	0.5	0.2
TW-0	0.5~1.5	1.0	0.5
TW-3	1.0~3.0	1.3	1.4
TW-5	2.5~5.0	1.3	1.5
TW-9	4.5~9.0	1.3	3.4
TW-15	9.0~15.0	1.3	3.8
TW-22	15.0~22.0	1.5	7.2
TW-30	22.0~30.0	1.5	7.6
TW-40	30.0~40.0	1.5	9.8
TW-50	40.0~50.0	1.5	10.4
TW-60	50.0~60.0	1.5	11.6
TW-70	60.0~70.0	1.5	11.8

HOSE REEL BALANCER SERIES



MODEL	Capacity (kg)	Stroke (m)	Weight (kg)	Hose DIA (φ mm)
HW-0	0.5~1.5	1.3	1.6	φ 6.5 / φ 10
HW-3	1.5~3.0	1.3	1.7	φ 6.5 / φ 10
HW-5	3.0~5.0	1.3	1.8	φ 6.5 / φ 10

- Functions both as balancer and hose reel

RETRACTOR SERIES



MODEL	Capacity (kg)	Stroke (m)	Weight (kg)
RW-0	0.5~1.5	2.0	0.5
RW-3	1.0~3.0	2.0	0.7
RW-5	2.5~5.0	2.0	0.9

- Tension easily adjustable using knob

MODEL	Capacity (kg)	Stroke (m)	Weight (kg)
TW-1R	0.5~1.5	1.5	0.3

- Tension easily adjustable using knob




★ Specifications and designs are subject to change at any time without notice.



Head Office
9-4, Nakaikogami 2-chome,
Ohta-ku, Tokyo 146-8555 Japan
Phone : +81-3-3755-1111 Fax : +81-3-3753-8791

► URL : www.nitto-kohki.co.jp/e ► E-mail : overseas@nitto-kohki.co.jp

Manufactured by
NITTO KOHKI-MIJIN CO.,LTD.



DISTRIBUTED BY